## **PCT**

(57) Abstract

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number: WO 99/60377
G01N 15/02, A61N 5/06	A1	(43) International Publication Date: 25 November 1999 (25.11.99)
<ul> <li>(21) International Application Number: PCT/US</li> <li>(22) International Filing Date: 19 May 1999 (</li> <li>(30) Priority Data: 60/085,941 19 May 1998 (19.05.98)</li> <li>(71) Applicant (for all designated States except US): SP INC. [US/US]; 6025A Unity Drive, Norcross, G (US).</li> <li>(72) Inventors; and</li> <li>(75) Inventors/Applicants (for US only): BAMBOT, [IN/US]; 650 Manor Glen Drive, Suwanee, G. (US). FAUPEL, Mark, L. [US/US]; 530 W Way, Alphretta, GA 30022 (US). ARCHE, Glent [US/US]; 2451 Stonecroft Way, Duluth, GA 30097.</li> <li>(74) Agent: FLESHNER, Mark, L.; Fleshner &amp; Kim, F 221200, Chantilly, VA 20153–1200 (US).</li> </ul>	Shabb A 300° Shabb A 300° Shabb A 300° Shabb A 300° (US).	BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published  With international search report.  Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
120 122 110 112 114 116 121 123 10 118		

An apparatus and method embodying the invention include utilizing a device with a limited number of interrogation devices to accomplish a large number of measurements on a target tissue (50). An instrument embodying the invention includes a plurality of detection devices (54) that are arranged in a predetermined pattern on a tissue contacting face of the instrument. The face of the instrument is located adjacent the target tissue (50), and a plurality of tissue characteristic measurement are simultaneously conducted. The detection devices (54) are moved to a new position, preferably without moving the tissue contacting face, and a second plurality of tissue characteristic measurements are simultaneously conducted. By conducting a series of measurements cycles in this manner, the ultimate resolution of the device is increased, while still obtaining a given resolution, which reduces potential cross-talk errors. Further, a plurality of tissue characteristics are simultaneously obtained from locations spaced across the target tissue (50) during each measurement cycle.